



Track Asphalt Pavers									
	Rhino RAP70T		Cat AP655F		Volvo P7110		Bomag CR462		
Engine									
Brand	Deutz		Cat		Volvo		Cummins		
Model	BF6L913		C4.4 Acert		D8		QSB6.7		
Emission Rating (optional)	Tier 2 (3 / 4)		Tier 4		Tier 4		Tier 3		
Displacement L (in3)	6	(372)	N/P	N/P	N/P	N/P	N/P	N/P	
Gross Engine Output Kw (Hp)	112	(150)	129	(173)	175	(235)	168	(225)	
Dimensions									
Min. Transport Height mm (ft)	2,888	(9)	2,929	(10)	N/P	N/P	N/P	N/P	
Standard Screed Transport Width mm (ft)	3,000	(10)	N/P	N/P	N/P	N/P	3,150	(10)	
Track Length on Ground mm (ft)	3,030	(10)	N/P	N/P	N/P	N/P	2,896	(10)	
Overall Length with Standard Screed mm (ft)	6,565	(22)	6,720	(22)	6,500	(21)	5,969	(20)	
Hopper Length mm (ft)	2,190	(7)	2,215	(7)	N/P	N/P	1,803	(6)	
Overall Machine Height mm (ft)	3,928	(13)	3,777	(12)	3,520	(12)	2,794	(9)	
Refill Capacities									
Fuel Tank L (gal)	190	(50.2)	278	(73.4)	354	(93.5)	273	(72.1)	
Performance									
Max. Travel Speed kph (mph)	2.9	(1.8)	N/P	N/P	16	(9.9)	15	(9.3)	
Rated Paving Width mm (ft)	3,000	(10)	3,306	(11)	3,000	(10)	3,150	(10)	
Extended Paving Width - Std Screen mm (ft) - (optional 9,000)	7,000	(23)	6,500	(21)	7,920	(26)	8,500	(28)	
Retracted Paving Width - Std Screen mm (ft)	3,000	(10)	N/P	N/P	N/P	N/P	N/P	N/P	
Driving System Type	Rubber Track		Tracked		Tracked		Tracked		
Auger Type	Twin Screws		N/P		N/P		N/P		
Conveyor Type	Twin Conveyors		N/P		N/P		N/P		
Weights									
Operating Weight with Screed kg (lbs)	19,500	(42,990)	15,584	(34,357)	19,006	(41,901)	15,740	(34,701)	

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.