



## Wheel Excavator

**RHINO REX60W**

**HYUNDAI 55W-9**

General		RHINO REX60W		HYUNDAI 55W-9	
Brand		Rhino		Hyundai	
Model		REX60W		55W-9	
Weight					
Operating Weight kg (lb)		5,980	(13,184)	5,550	(12,236)
Engine					
Engine Make		Rhino		YANMAR	
Engine Model		A498BPG		4TNV98	
Net Horsepower kW (hp)		45	(60)	43	(58)
Number of Cylinders		4		4	
Piston Displacement L (cu. In)		3.2	(195)	3.3	(201)
Hydraulics					
Max. Flow ltr/min (gpm)		48	(13)	110	(29)
Implement Relief Valve Setting Mpa (psi)		18	(2,611)	22	(3,191)
Undercarriage					
Max. Travel Speed: High Kph (mph)		N/P	N/P	27	(17)
Tires		12-16.5		12-16.5	
Swing					
Swing Speed (rpm)		13		9	
Performance					
SAE Bucket Digging Force at Power Max. kg (lb)		5,914	(13,038)	3,770	(8,311)
Dimensions					
Overall Height to Top of Cab mm (ft)		2,905	(9.5)	2,850	(9.4)
Ground Clearance, Counterweight mm (in)		290	(11)	N/P	N/P
Swing Radius mm (ft)		N/P	N/P	1,650	(5.4)
Wheelbase mm (ft)		2,345	(92.3)	N/P	N/P
Overall Width mm (ft)		2,035	(6.7)	1,925	(6.3)
Working Range					
Max. Digging Depth mm (ft)		2,857	(9.4)	3,500	(11.5)
Max. Vertical Wall Digging Depth mm (ft)		2,250	(7.4)	N/P	N/P
Max. Digging Depth at 1,890 mm (6 ft) Flat Bottom mm (ft)		2,745	(9.0)	N/P	N/P
Max. Digging Reach at Ground Level mm (ft)		5,776	(19.0)	5,980	(19.6)
Max. Digging Height mm (ft)		N/P	N/P	6,070	(19.9)
Max. Dumping Height mm (ft)		3,810	(12.5)	4,340	(14.2)
Capacities					
Refill Capacity - Fuel Tank L (gal)		100	(26.4)	125	(33.0)
Refill Capacity - Coolant L (gal)		13	(3.4)	10	(2.5)
Refill Capacity - Engine L (gal)		18	(4.8)	12	(3.1)
Refill Capacity - Final Drive, Each L (gal)		N/P	N/P	2	(0.4)
Refill Capacity - Hydraulic Tank L (gal)		100	(26.4)	70	(18.5)

Equipment specifications and images may change without notice from Rhino Equipment Group Inc.

Rhino Equipment assumes no responsibility or liability for any information, specifications, condition reports, photography or information of the competitive equipment. Rhino Equipment is not responsible for the information contained or not contained regarding the competitive equipment.